

Single Pole Devices and Temporary Power  
 Series 16 - 300 and 400A, 600V AC/250V DC  
 Paralleling Tee

# HUBBELL

## Ordering Information

Description	Device Color	UPC	Catalog Number
Paralleling "T" Connector (Female-Male-Male)	Green	783585113135	HBLPTGN



## Standards

UL 498 and UL1691  
 UL Enclosure Types 3R, 4X, 12

## Specifications


Product Type	Ts" and Tri-Taps
Tee and Tap Type	Paralleling "T" Fitting
Body Material	Thermoplastic Elastomer
Contact Material	Brass

## Performance

Electrical	
Amperage Rating	400A Maximum
Voltage Ratings	600V AC Maximum; 250V DC Maximum

## Mechanical

Product Identification	Ratings are a permanent part of the device
------------------------	--



## Online Resources

Customer Use Drawing  
 eCatalog  
 Installation Instructions

Distributor:



Phone: 407-857-8770  
 Fax: 407-857-8771  
 Email: sales@techni-lux.com  
 www.techni-lux.com

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

