

Archibar *line*



ARCHIBAR 250



r+g+b+w

Discover the new family of ARCHIBAR. The last born ARCHIBAR 250 is a powerful led bar fixture for indoor use.

64 LUXEON REBEL 5W Led's!
16 units (RGBW) with four separate groups for fantastic result of light games.

very powerful



64 led fixture



ARCHIBAR 250 specifications

SOURCE (64 LUXEON REBEL 5W Led's)
16 units (RGBW) with four separate groups

OPTIC
25mm lenses standard beam (25°)
On request: narrow beam lenses 10° and wide beam lenses (40°)
to be confirmed at order

TILT
Tilt: 120°

CONTROL
Standard interface: RS-485; opto-couplet input.
Protocol: USITT DMX 512 - 21 channels

SETUP AND CONFIGURATION
4 multifunction keys and LCD
Internal 22 preset with master/slave function

POWER SUPPLY
Switching power supply (universal main voltage)
Rated voltage: 100-240V~; 50-60Hz
Rated power: 300W
Rated current: 1,5A @ 230V

DMX CHANNELS

ch1 = led group 1 - red	ch12 = led group 3 - white
ch2 = led group 1 - green	ch13 = led group 4 - red
ch3 = led group 1 - blue	ch14 = led group 4 - green
ch4 = led group 1 - white	ch15 = led group 4 - blue
ch5 = led group 2 - red	ch16 = led group 4 - white
ch6 = led group 2 - green	ch17 = dimmer
ch7 = led group 2 - blue	ch18 = strobe
ch8 = led group 2 - white	ch19 = led fade speed
ch9 = led group 3 - red	ch20 = rainbow
ch10 = led group 3 - green	ch21 = balanced white
ch11 = led group 3 - blu	

PHYSICAL
Width: 1005 mm
Depth: 180 mm (max)
Height: 255 mm (max)
Weight: 8,7 kg.

available version:
art. 0901: rgbw ARCHIBAR 250



The separate groups of led to create infinite scenes and games.

4 led groups

to create

numberless scenes





ARCHIBAR 150/C



Archibar 150/C is a Studio Due powerful IP 67 wash led light fixture!

Dashing and compact, Archibar 150 is made in aluminium and is equipped with 16 units (rgbw) of 3W Luxeon Rebel led's each. The optics, realized in special material, allow brilliant light and a very homogeneous beam. Standard optics are 25°. On request, to be confirmed at order, is possible to have the wide optics 40° or the narrow optics 10°.

For permanent wall installations is possible to remove the floor bracket and fix the unit on a surface with the optional wall bracket art. **AB-WB**. Over 180° tilt regulation.



Inside, the microswitches provide to set-up the fixture.

ARCHIBAR 150/C specifications

SOURCE (64 Luxeon Rebel 3W Led's)
16 units (RGBW) with four groups

OPTIC
25mm lenses standard beam (25°)
On request: narrow beam lenses 10° and wide beam lenses (40°)
to be confirmed at order

TILT
Tilt: 120°

CONTROL
Standard interface: RS-485; opto-couplet input.
Protocol: USITT DMX 512 - 9 channels

SETUP AND CONFIGURATION
Inside with microswitches
Internal 12 preset with master/slave function

IP RATE
IP 67 fixture, main power and DMX cable connections

POWER SUPPLY
Switching power supply (universal main voltage)
Rated voltage: 100-240V~; 50-60Hz
Rated power: 180W
Rated current: 1A @ 230V

DMX CHANNELS
ch1 = red
ch2 = green
ch3 = blue
ch4 = white
ch5 = strobe
ch6 = dimmer
ch7 = led fade time
ch8 = rainbow
ch9 = white balanced

PHYSICAL
Width: 1005 mm
Depth: 190 mm (max)
Height: 200 mm
Weight: 8,5 kg.

IP 67 rate



Archibar 150 is equipped with floor bracket for easy installations.

cable connection included



For permanent installations is possible to remove the floor bracket and fix the unit on a surface. Anyway you have 120° tilt regulation.

available version:
art. 0806: rgbw ARCHIBAR 150/C

available accessories:
art. AB-WB: wall bracket to fix the unit on wall



ARCHIBAR 50

IP 67 rate

r+g+b+w



very compact



ARCHIBAR 50 specifications

SOURCE (20 Luxeon Rebel 3W Led's)
5 units (RGBW) with four groups

OPTIC
25mm lenses standard beam (25°)
On request: to be confirmed at order
narrow beam lenses 10° and wide beam lenses (40°)

TILT
Tilt: 120°

CONTROL
Standard interface: RS-485; opto-couplet input.
Protocol: USITT DMX 512 - 9 channels

SETUP AND CONFIGURATION
Inside with microswitches
Internal 12 preset with master/slave function

IP RATE
IP 67 fixture, main power and DMX cable connections

POWER SUPPLY
Switching power supply (universal main voltage)
Rated voltage: 100-240V~; 50-60Hz
Rated power: 60W
Rated current: 0,3A @ 230V

DMX CHANNELS
ch1 = red
ch2 = green
ch3 = blue
ch4 = white
ch5 = strobe
ch6 = dimmer
ch7 = led fade time
ch8 = rainbow
ch9 = white balanced

PHYSICAL
Width: 380 mm
Depth: 190 mm (max)
Height: 205 mm (max)
Weight: 4 kg.



For permanent wall installations is possible to remove the floor bracket and fix the unit on a surface with the optional wall bracket art. **AB-WB**. Over 180° tilt regulation.

available version:
art. **0808**: rgwb ARCHIBAR 50

available accessories:
art. **AB-WB**: wall bracket to fix the unit on wall



Head Quarter: STUDIO DUE s.r.l.
Str. Poggino, 100 - 01100 Viterbo (Italy)
tel. +39.0761.352520 (4 lines)
fax +39.0761.352653

STUDIO DUE UK
3 Encon Court, Owl Close
Moulton Park Industrial Estate
Northampton (England) UK - NN3 6 HZ
tel. +44.1933.650.820

STUDIO DUE Far East LTD
Unit 13 7/F - Heng Ngai Jewelry Centre
4 Hok Yuen Street East - Hunghom Kowloon (Hong Kong)
tel. +852.29542141 fax +852.23302515

STUDIO DUE Lighting Technology (Shen Zhen) LTD

studiodue.com

emotion and creativity in light

Studio Due