

Single Pole Devices and Temporary Power
 Series 16 - 300 and 400A, 600V AC/250V DC
 Gender Reversing Devices

HUBBELL

Ordering Information

Description	Device Color	UPC	Catalog Number
Double Female Coupler (Female-Female)	Blue	783585002903	HBLDFBL




Standards

UL and cUL Listed
 UL Enclosure Types 3R, 4X, 12
 UL 498 and UL1691

Specifications

Product Type	Accessories
Accessory Item	Double Male Coupler
Body Material	Thermoplastic Elastomer
Contact Material	Brass



Performance

Electrical	
Amperage Rating	400A Maximum
Voltage Ratings	600V AC Maximum; 250V DC Maximum

Mechanical	
Product Identification	Ratings are a permanent part of the device

Online Resources

Customer Use Drawing
 eCatalog
 Installation Instructions

Distributor:



Phone: 407-857-8770
 Fax: 407-857-8771
 Email: sales@techni-lux.com
 www.techni-lux.com

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

