

Single Pole Devices and Temporary Power

300 and 400A, 600V AC/DC

Angled Receptacles, Stud Type Through Hole Mounting



Ordering Information

| Description                                                                       | Color | UPC          | Catalog Number |
|-----------------------------------------------------------------------------------|-------|--------------|----------------|
| 400 amp Panel Mount, thermoplastic elastomer, mates with 300 and 400 amp Inlines. | Black | 783585511580 | HBLFRASBK      |

Listings

UL and cUL Listed  
UL Enclosure Types 3R, 4X, 12  
National Electric Code (NEC), ANSI/NFPA 70

Specifications

|                          |                                 |
|--------------------------|---------------------------------|
| Base Compound            | Thermoplastic Elastomer (TPE)   |
| Contact Material         | Brass                           |
| Retaining Screw Material | Nylon                           |
| Mounting Hole            | 4x #10-32                       |
| Termination              | (2) 7/32 Socket Head Set Screws |

Performance

| Electrical             |                                        |
|------------------------|----------------------------------------|
| Amperage Rating        | 400A Maximum                           |
| Voltage Rating         | 600V AC/DC Maximum                     |
| Mechanical             |                                        |
| Product Identification | Ratings are a permanent part of device |
| Terminal Accommodation | #4 to 4/0 AWG                          |
| Environmental          |                                        |
| Flammability           | HB per UL94 or CSA 22.2. 0.17          |



Online Resources

Customer Sales Drawings  
eCatalog  
Installation Instructions



Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

Distributor:



Phone: 407-857-8770  
Fax: 407-857-8771  
Email: sales@techni-lux.com  
www.techni-lux.com

**Distributor:**

Phone: 407-857-8770

Fax: 407-857-8771

Email: [sales@techni-lux.com](mailto:sales@techni-lux.com)

[www.techni-lux.com](http://www.techni-lux.com)

