

Twist-Lock® Devices
15A, 250V, 2 Pole, 3 Wire Grounding
Insulgrip® Connector

HUBBELL

Features

- Ribbed nylon housing provides secure, impact and chemical resistant grip
- Superior cord grip design protects terminations from excess strain
- Integral VARI-SIZE insert accommodates a wide range of cord diameters

Ordering Information

Description	Cord Diameter	UPC	Catalog Number
Black and white nylon.	.230"-.720" (5.8-18.3)	783585170107	HBL4579C

Listings

Listed to UL 498
Fed.Spec. W-C-596
Certified to CSA C22.2 No.42

Specifications

Housing / Cord Clamp	Nylon
Terminal Retainer	Clear polycarbonate
Contacts	Brass
Terminal Screws	#8-32 Brass (Phillips / Slotted / Robertson)
Terminal Clamp	Cold rolled steel – nickel plated
Assembly Screws	Steel - nickel plated

Performance

Electrical

Current Interrupting Certified for current interrupting at full rated current
Dielectric Voltage Withstands 2,000V minimum

Mechanical

Terminal Accommodation #18 - #10 AWG stranded copper wire only.




Terminal Identification Terminals identified in accordance with UL 498

Environmental

Flammability HB or better per UL94 or CSA 22.2 No. 0.6
Moisture Resistance IP20 Suitability
Operating Temperatures Maximum Continuous 75°C Minimum -40°C (w/o impact)



15A 250V
NEMA L6-15R
UL/CSA



Accessories

Plug	HBL7545C
Weatherproof Boot	HBL6024
Flanged Inlet	HBL7524C
Weatherproof Boot	HBL6023

Resources

Customer Use Drawing
eCatalog



Distributor:
Phone: 407-857-8770
Fax: 407-857-8771
Email: sales@techni-lux.com
www.techni-lux.com

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

