



Product Data Sheet

Product Type

IP65 RJ45 Socket

Product Model

SE8FDYH-63-B-NS

Customer Name

Manufacturer	Prepared	Checked	Approved

Customer	Received	Checked	Confirmed

Distributor:



Phone: 407-857-8770

Fax: 407-857-8771

Email: sales@techni-lux.com

www.techni-lux.com

Above specifications and information may have tolerances and have been updated.
Every effort has been made to ensure correctness upon release of this data sheet.

All Rights Reserved 2023



sales@seetronic-group.com
www.seetronic.com

Product Data Sheet

Product Type	IP65 RJ45 Socket	
Product Model	SE8FDYH-63-B-NS	
Product Features		
<ul style="list-style-type: none">➤ New anti-leakage upgraded series with waterproof grade IP65➤ Better protection and extends the service life of the equipment➤ It can withstand air pressure of 0.2Mpa and no leakage at the rear when the waterproof cover is not in use➤ D-shape panel connector with black metal flange and standard D-style installation size➤ Install from the front the panel➤ The rear end is 180° 8-pin terminal➤ Conforms to Class D according to TIA/EIA568B and ISO/IEC11801 standards➤ Fast locking and unlocking for the front and rear feed-through type, providing a guaranteed reliability for continuous and stable signal transmission under moving conditions		



Product Data Sheet

Product Parameters

Item	Specification
Connection type	RJ45
Gender	Female

Electrical Parameters

Item	Specification
Contact resistance	< 10 mΩ
Rated current	1.5 A
Rated voltage	50 V
Insulation resistance	≥ 0.5GΩ
Dielectric strength	1 KV DC
Frequency range	1~100 MHz
Transmission performance	Class D

Product Data Sheet

Mechanical Parameters

Item	Specification
Insertion force	≤ 20 N
Chassis shape	D-shape
Service life	> 1000 mating cycles
Locking device	Latch lock

Material and Environmental Parameters


Item	Specification
Housing	Zinc alloy
Housing plating	Black plating
Contacts	Copper alloy
Contact surface	Au
Protection degree	IP65
Temperature range	-30°C ~ +80°C

Standards and Certifications

Standards	TIA/EIA 586B, IEC11801
-----------	------------------------

Product Data Sheet

Product Drawing



Unit: mm

Packaging Method

1 pc per bag (include 1 pc each socket and waterproof gasket)
50 pcs per inner carton, 5 inner cartons per master carton (250 pcs per master carton)

Product Data Sheet


Accessory

- No accessories
- Screws and Nuts
- Back fastener plate
- Waterproof gasket

Assembly Instructions

(1) First, match the waterproof gasket with the socket, and then install the socket in the open hole of the box. Finally, tighten the screws with 0.5 Nm torque in a clockwise direction.

(Note: Panel thickness 1.5 ~ 4mm)



(2) Wiring diagram

