

Locking Devices

Insul-Lock Plus Devices

20A Connector

HUBBELL

Features

- Insulgrip style body design
- Accepts up to #12/3 AWG SO cable
- UL Enclosure type 4X and IP65 rated
- Disconnectable under load
- Multiple strain relief collets to accommodate wide range of cables
- Industry standard mating

Ordering Information

Description Locking female cable connector, power in, screw terminals	UPC 783585580852	Catalog Number HBLFC
Cord Size Accepts #18/3 up to #12/3 AWG SO Cable	Color Black	



Listings

UL Recognized to US and Canadian standards
UL50E Encl. type 4X when mated to Insul-lock plus HBLMC
or when mated to HBLMP or HBLMPD in combination with HBLMPC or HBLMPDC
IP65 rated when mated to Insul-lock plus HBLMC
or when mated to HBLMP or HBLMPD in combination with HBLMPC or HBLMPDC

Specifications

Body	Thermoplastic
Contacts	Copper Alloy
Weight	0.1

Performance

Electrical	
Amperage	20A
Voltage	up to 250V AC

Distributor:



Phone: 407-857-8770

Fax: 407-857-8771

Email: sales@techni-lux.com

www.techni-lux.com

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

