

Product Type	I G6!7 GcW_Yh	
Product Model	GG77A78:!\$%	
Customer Name		

Manufaatuwaw	Prepared	Checked	Approved
Manufacturer			

Curata ma a r	Received	Checked	Confirmed
Customer			



Phone: 407-857-8770
Fax: 407-857-8771
Email: sales@techni-lux.com
www.techni-lux.com





Product Type	USB-C Socket	SEETRONIC O
Product Model	SCCMCDF-01	

#### **Product Features**

- Reliable and compact USB-C female-to-female connector
- High current capacity, rated at 5A
- Dual 24P full core ports
- ➤ IP65 waterproof and airproof
- Meets standard USB 3.1



#### **Product Parameters**

Item	Specification
Connection Type	USB-C Socket
Gender	Female

#### **Electrical Parameters**

Item	Specification
Contacts Number	24
Contact resistance	≤ 50 mΩ
Rated contact	5 A

#### **Mechanical Parameters**

Item	Specification
Service life	> 10000 mating cycles



#### **Material and Environmental Parameters**


Item	Specification
Contacts	Cu alloy
Contact plating	Au
Housing	PA
Flame-retardant grade	UL 94 -V0
Temperature range	-40°C ~ +80°C

Standards and Certifications	

Standards	USB3.1
-----------	--------



#### **Product Drawing**



#### **Packaging Method**

1 pc per bag (including 1 socket and 1 waterproof cover) 300 pcs per inner carton, 5 inner cartons per master carton (1500 pcs per master carton)

#### **Accessory**

☑ No accessories□ Back fastener plate□ Screws and Nuts□ Other



#### **Assembly Instructions**

First, make sure the waterproof cap is assembled on the rear side of the socket.

Then, install the socket on the front side of the panel.

Finally, tighten the screws with 0.5 N-m torque in clockwise direction.

