

P-5 W White Wash

Specifications		
Optics	Light source	44 x High power 10W Cool White LEDs (6,400K)
	LEDs expected lifetime	50,000 hours*
	Interchangeable lens option	15°, 21° & 43°
Photometric	Light output	33,100 lumen (43° lens)
	Efficacy	81 lm/W
Features	Pan/Tilt	+ / - 90°
Electrical	AC Power	208 - 240 V Nominal 50/60 Hz
	Maximum power consumption	450 W (all LEDs on)
	Typical power consumption	420 W (all LEDs on)
	Power factor	0.98 PF (230 V)
Programming and Control	Protocol	USITT DMX512 A
	Setting and addressing	Wireless DMX (LumenRadio) RDM Stand alone mode (programmable by RFID) Oled graphical display / 4 buttons Software upgradeable via Uploader cable (P/N:83062011)
	DMX channels	1 or 2 DMX channels
Physical	Dimensions (L x H x W)	497 x 268 x 122 mm (19.6 x 10.6 x 4.8 in)
	Weight	8.9 kg (19.6 lbs.)
	Material	Aluminium
	Lens	PE and tempered glas front
	IP class	IP65
Installation	Mounting	Any, but facing 100% down for permanent installation
	Rigging possibilities	Floor stand (included) or hanging (Omega Clamps included)
	Safety features	Bottom mount for Safety wire
Thermal	Temperature range, Operating	-10° – 40°C (14° – 104°F)
	Temperature range, Start-up	-10° – 40°C (14° – 104°F)
	Humidity (max.)	98%
	Cooling	Active, Forced air, temperature-regulated, low noise
Connections	DMX data in/out	IP65 Neutrik HD locking XLR 5-pin cable 0.5m for DMX in and out Power cable 0.5m with bare ends
Certified to Conforms to	CSA Std. C22.2 No. 166	
	UL Std. 1573	
	2006/95/EC: Low Voltage Directive	EN 60598-1, EN 60598-2-17, EN 62471
	2004/108/EC: EMC Directive	EN 55103-1, EN 55103-2, EN 61000-3-2, EN 61000-3-3
	RoHS2 Directive	2011/65/EU
Included Items	Included Items	Floor Stand (incl. screws) 2 pcs Omega brackets Wireless DMX G4 antenna User manual Neopren pouch
Fixtures and Accessories	Fixtures	Order no: 80030521 - P-5 W Wash Light (43°) Order no: 80030520 - P-5 W Wash Light (21°) Order no: 80030516 - P-5 W Wash Light (15°)
	Lens/s	Order no: 83061104 - P-5, Lens kit (43°) Order no: 83061103 - P-5, Lens kit (21°) Order no: 83061102 - P-5, Lens kit (15°)
	Brackets	Order no: 83060603 - BCC-2 Dual bracket Order no: 83060604 - BCC-4 Quad bracket Order no: 83060602 - Omega bracket
	Floorstand	Order no: 83060610 - Floorstand for P, Q and X series with 1/4-turn fasteners
	Barndoor	Order no: 83061119 - Accessory Holder P Series Order no: 83061120 - Barndoor 4-way Order no: 83061121 - Barndoor 8-way Order no: 83061122 - Color frame
	Cables	Order no: 83062011 - SGM USB uploader cable
	Flight case	Order no: 82051501 - Flight case for 4 pcs of P-5/Q-7/X-5

*(Figure provided by manufacturer and obtained under manufacturer's test conditions)

Distributor:



Phone: 407-857-8770
Fax: 407-857-8771
Email: sales@techni-lux.com