

## R-2 W, 4000K Rail-Light

Specifications		
Optics	Light source	4000K
	LEDs expected lifetime	50,000 hours*
Photometric	Interchangeable lens option	25° / 35°
	Light output	3900lm
	Optical efficacy	125 lm/W
Features	CRI	>80
	Pan/Tilt	330° / 270°
Electrical	AC Power nominal	100 - 240 V 50/60 Hz
	AC Power max rating	90-264V 50/60Hz
	Maximum power consumption	35W
	Typical power consumption	33W
	Power factor	0.90 PF (230 V)
Programming and Control	Protocol	CRMX, W-DMX™ G2, W-DMX G3, W-DMX G4, W-DMX G4S
	Setting and addressing	Wireless DMX (LumenRadio) Software upgradable via wireless
	DMX channel	1
Physical	Dimensions (L x W)	224 x 187 mm (8,8 x 7,4 in)
	Spot diameter	Ø 104 mm (4,1 in)
	Weight	1 kg (2,2 lbs.)
	Material	Aluminium, Stainless steel, ABS
	Lens	PMMA
	IP class	IP20
Installation	Mounting	Track mount
	Orientation	Any
Thermal	Temperature range, Operating	-10° to +40°C (-14° to +104°F)
	Humidity (max.)	95%
	Cooling	Passive cooling
Connections	Power	Track mount adapter
	DMX	Wireless (Lumen Radio)
Conforms to	2006/95/EC: Low Voltage Directive	EN 60598-1, EN 60598-2-1, EN 60598-2-17, EN 62471
	1999/5/EC: R&TTE Directive	EN301489-1, EN301489-3, EN300328
	RoHS2 Directive	2011/65/EU
Included Items	Included Items	User manual Pin key tool
	Fixtures and Accessories	Order no: 84010109 - R-2 W, 4000K, white, 25 deg Order no: 84010110 - R-2 W, 4000K, black, 25 deg Order no: 83062011 - SGM USB uploader cable Order no: 80070229 - Lumen Radio transmitter DMX (Only) Order no: 80070230 - Lumen Radio transmitter DMX/RDM

\*(Figure provided by manufacturer and obtained under manufacturer's test conditions)

Distributor:



Phone: 407-857-8770  
Fax: 407-857-8771  
Email: sales@techni-lux.com