

PORTABLE FLUORESCENT LIGHTING

Model DFL-2/40 | Model DFL-4/40



Ballast box & control panel

The lamps can be controlled remotely from a ballast box with control panel.



Ballast box 2x40w

Ballast box & control panel

The lamps can be controlled remotely from a ballast box with control panel.




Ballast box 4x40w

2/40 or 60w Fluorescent Lamps T-12 1.20m(4ft) Model DFL-2/40

PHOTOMETRIC DATA

POWER FLO DFL-2/40 | With 2 Fluorescent F40T12 lamps




Distance (mts)	1.00	1.50	2.00	2.50	3.00	3.50
Luminance (lux)	1950	870	512	360	210	150

4/40 or 60w Fluorescent Lamps T-12 1.20m(4ft) Model DFL-4/40

PHOTOMETRIC DATA

POWER FLO DFL-4/40 | With 4 Fluorescent F40T12 lamps



Distance (mts)	1.00	1.50	2.00	2.50	3.00	3.50
Luminance (lux)	3000	1350	780	570	360	270

LAMPS

CODE GE	WATTS	INITIAL LUMENS	MEAN LUMENS	LIFE HS.	LONG. MM(FT)
F40T12/Cinema 32/CVG	40	2000	1600	20000	1200 (4)
F40T12/Cinema 55/CVG	40	1950	1560	20000	1200 (4)
F40T12/Cinema 32/HO/CVG	60	2900	2030	15000	1200 (4)
F40T12/Cinema 55/HO/CVG	60	2820	1970	15000	1200 (4)

LAMPS

CODE GE	WATTS	INITIAL LUMENS	MEAN LUMENS	LIFE HS.	LONG. MM(FT)
F40T12/Cinema 32/CVG	40	2000	1600	20000	1200 (4)
F40T12/Cinema 55/CVG	40	1950	1560	20000	1200 (4)
F40T12/Cinema 32/HO/CVG	60	2900	2030	15000	1200 (4)
F40T12/Cinema 55/HO/CVG	60	2820	1970	15000	1200 (4)

POWER FLO DFL-2/40	
	L 320mm. (12.61")
	W 1320mm. (52.00")
	H 330mm. (13.00")
	kg 10.00Kg. (22.05 Lbs.)
	1350x400x300mm. (53.15"x15.75"x11.81")

POWER FLO DFL-4/40	
	L 380mm. (14.97")
	W 1320mm. (52.00")
	H 380mm. (14.97")
	kg 13.00Kg. (28.66 Lbs.)
	1350x500x300mm. (53.15"x19.69"x11.81")

ACCESSORIES



ORDERING INFORMATION

DFL-2/40 Power Flo with 2 lamps T-12 40 or 60 Watts for DMX/Local DIM. control, 120-230v.

ACCESSORIES



ORDERING INFORMATION

DFL-4/40 Power Flo with 4 lamps T-12 40 or 60 Watts for DMX/Local DIM. control, 120-230v.