

# P-628

**Shurtape®**  
TRUE TO YOUR WORK™

## PROFESSIONAL GRADE, COATED GAFFER'S TAPE

### TYPICAL APPLICATIONS

- For general use in the convention, hospitality, exhibition and trade show industries, as well as for bundling wires, taping down lighting and props, and masking silk screen frames in the audio/visual, television, photography, theatrical and motion picture industries
- Can also be used for protection and book-binding, color-coding, labeling and marking

### PRODUCT FEATURES

- High tack, tensile strength and holding power
- Writable surface
- Durable and conformable
- Hand-tearable in machine and cross directions

### CONSTRUCTION

Overall Grade/Function: Professional  
Backing: Matte-finish coated cloth  
Adhesive: Synthetic rubber

### STANDARD WIDTH(S)

48 mm    72 mm

### STANDARD LENGTH(S)


50 m

Contact your Shurtape sales representative for other available sizes

### STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

### COLOR(S)



### PHYSICAL PROPERTIES    STANDARD    METRIC

Tensile Strength	50 lbs/in width	87.6 N/10 mm
Adhesion to Stainless Steel	75 oz/in width	8.21 N/10 mm
Thickness	10.75 mils	0.27 mm
Elongation	4%	4%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



Shurtape Technologies, LLC  
ISO 9001 CERTIFIED QUALITY SYSTEM

Distributor:



Phone: 407-857-8770

Fax: 407-857-8771

Email: [sales@techni-lux.com](mailto:sales@techni-lux.com)

[www.techni-lux.com](http://www.techni-lux.com)