



MSD Platinum (Touring/Stage)

MSD Platinum 400S Flex 1CT/8

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- · Lamp contains mercury. Manage in Accord with Disposal Laws. See: www.lamprecycle.org or 1-800-555-0050

Product data

General Information		
Base	-[-]	
Operating Position	Universal [Universal]	
Main Application	Stage/Touring	
Life to 50% Failures (Nom)	2000 h	
Life to 50% Failures entertainment cycle (Nom)	6000 h	
System Description	Reflector E21.9 TCM	
Light Technical		
Color Code	2	
Initial lumen (Nom)	26200 lm	
Chromaticity Coordinate X (Max)	313	

Chromaticity Coordinate X (Min)	280	
Chromaticity Coordinate X (Nom)	297	
Chromaticity Coordinate Y (Max)	316	
Chromaticity Coordinate Y (Min)	290	
Chromaticity Coordinate Y (Nom)	298	
Correlated Color Temperature (Nom)	8000 K	
Luminous Efficacy (rated) (Nom)	47 lm/W	
Operating and Electrical		

470 W

Datasheet, 2020, December 1	data subject to change

Power (Rated) (Nom)
Voltage (Max)

MSD Platinum (Touring/Stage)

Voltage (Min)	85 V	
Controls and Dimming		
Dimmable	Yes	
Mechanical and Housing		
Cap-Base Information	na [-]	
Luminaire Design Requirements		
Bulb Temperature (Max)	900 ℃	
Pinch Temperature (Max)	350 °C	

Product Data	
Order product name	MSD Platinum 400S Flex 1CT/8
EAN/UPC - Product	8718699651985
Order code	343913
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	8
Material Nr. (12NC)	928496505314
Net Weight (Piece)	138.000 g

Dimensional drawing

, D ,

Product	D (max)	0	C (max)
MSD Platinum 400S Flex 1CT/8	58.5 mm	1.2 mm	72 mm

MSD Platinum 400S Flex

