

8. TRANSPORTATION DATA

D.O.T.: Not Regulated
Reportable Quantity: not applicable
Freight Classification: 65 Petroleum oil, N.O.I.B.N.
Special Transportation Notes: none

9. COMMENTS

This product is a fully refined white mineral oil meeting the requirements of the National Formulary XVII and the requirements of the Food and Drug Administration as per CFR 172.878.

10. LABEL INFORMATION

This product is made in a manner to insure quality, purity and stability. Handle carefully to preserve its original quality. May contain up to 10 ppm tocopherols as stabilizer. Hazard warning label not required under OSHA Hazard Communication Standard 29 CFR 1910.1200.

SPILLS OR LEAKS: Shut off leak and dike up spills. Absorb with an inert material such as sand, earth, or vermiculite, and dispose of in compliance with Federal, State, and local regulations.

FOR MANUFACTURING USE ONLY. SEE MATERIAL SAFETY DATA SHEET FOR DETAILED INFORMATION.

ATTENTION: Never use pressure to empty; drum is not a pressure vessel. When empty, drum may have vapor or product residue. Residual vapors may explode on ignition; do not puncture, drill, grind, or weld on or near this container.

Approved by: Kenneth Blair
Title: MANAGER, REGULATORY AFFAIRS

We believe the statement, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.

Material Safety Data Sheet

Techni-Lux, Inc.
Phone: 407-857-8770

ORLANDO, FL 32824-7046
www.techni-lux.com


Revision Date: 10/01/97

Printed: 5/03/01

PRODUCT CODE: FF-ELITEHAZE10

PRODUCT NAME: Elite Haze

| HAZARD RATINGS |
|------------------|
| N 4- Extreme |
| F 3- High |
| P 2- Moderate |
| A 1- Slight |
| 0- Insignificant |



1. DIVISION AND LOCATION

Emergency Telephone Number: (412) 756-2210
Transportation Emergency:
CHEM TREC 1 (800) 424-9300 (U.S. and Canada)

2. CHEMICAL AND PHYSICAL PROPERTIES

Formula: a mixture of liquid hydrocarbons refined from petroleum
Chemical Name: mineral oil blend
Hazardous Decomposition and Products: carbon monoxide and carbon dioxide from burning.
Incompatibility (keep away from): strong oxidizers such as hydrogen peroxide, bromine, and chromic acid.
Toxic and Hazardous Ingredients: none
Form: viscous liquid
Odor: none
Appearance: clear
Color: colorless
Specific Gravity (water=1): less than 1 at 15° C
Boiling Point: greater than 230° C (450° F)
Melting Point: not applicable
Solubility in Water (by weight %): negligible at 25° C

2. CHEMICAL AND PHYSICAL PROPERTIES (con't)

Volatile (by weight %): 0 at 25° C
Evaporation Rate: 0 at 25°C
Vapor Pressure (nm Hg at 20°C): less than .005
Vapor Density (air=1): not applicable
pH (as is): not applicable
Stability: Product is stable under normal conditions
Viscosity SUS at 100°F: less than 100

3. FIRE AND EXPLOSION DATA

Special Fire Fighting Procedures:

Wear self-contained breathing apparatus. Water spray is an unsuitable extinguishing agent. (See Extinguishing Agents)

Unusual Fire Explosion Hazards: none

Flashpoint: (Method Used- ASTM D-92) greater than 130°C (265°F)

Flammability limits %: no data available

Extinguishing agents: Drychemical or Waterfog or CO2 or Foam or Sand/Earth. Closed containers exposed to fire may be cooled with water.

4. HEALTH HAZARD DATA

PERMISSIBLE CONCENTRATIONS (AIR): If used in applications where a mist may be generated, observe a TWA/PEL of 5 mg/m3 for mineral oil mist (OSHA and ACGIH).

CHRONIC EFFECTS OF OVEREXPOSURE: no data available

ACUTE TOXICOLOGICAL PROPERTIES: no data available

EMERGENCY FIRST AID PROCEDURES:

EYES: Flush with large amounts of water for at least 15 minutes. If irritation persists, call a physician.

SKIN CONTACT: Wash with soap and water.

4. HEALTH HAZARD DATA (con't)

INHALATION: Not applicable

IF SWALLOWED: Contact a physician immediately. DO NOT induce vomiting. (Vomiting may cause Aspiration into lungs resulting in chemical pneumonia.)

5. SPECIAL PROTECTION INFORMATION

Ventilation Type Required (Local, mechanical, special): Local if necessary to maintain allowable PEL (permissible exposure limit) or TLV (threshold limit value)

Respiratory Protection (Specific type): none

Protective Gloves: none

Eye Protection: chemical safety goggles

Other Protective Equipment: none

6. HANDLING OF SPILLS OR LEAKS

PROCEDURES FOR CLEAN-UP:

Shut off leak and dike up large spills. Absorb with an inert material such as earth, sand or vermiculite. Sweep up and dispose of in accordance with Federal, State and local regulations.

WASTE DISPOSAL:

Dispose of in accordance with all applicable Federal, State and local regulations.

7. SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Keep away from heat and flames. Do not store near strong oxidizing agents.

Maximum Storage Temperature: 66°C (150°F)